kelso coatings

CN2000B Waterproof Material

Safety Data Sheet According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Date of issue: 12/13/2019

Revision date: 12/13/2019 Version: 1.0

SECTION 1: Identification	
1.1. Identification	
Product form	: Mixture
Product name	: CN2000B Waterproof Material
1.2. Relevant identified uses of the	e substance or mixture and uses advised against
Use of the substance/mixture	: Concrete waterproofing; Efficiency waterproof material
Restrictions on use	: For professional use only
1.3. Details of the supplier of the s	safety data sheet
Manufacturer Tianjin Hi-Tech Industry Park ZHONGHE No.168, Jintang Road, Hedong District,T 300180 T: 86-22-84801243 Fax: 86-22-24965149 URL: <u>http://www.zhonghe2000.com</u> E-mail: <u>zhonghe2000b@163.com</u>	
1.4. Emergency telephone numbe	r
Emergency number	: (416) 574-2092
SECTION 2: Hazard identification	
2.1. Classification of the substance	
Eye Dam. 1 STOT RE 2 2.2. Label elements GHS labelling	
Hazard pictograms (GHS)	
	GHS05 GHS08
Signal word (GHS)	: Danger
Hazard statements (GHS)	 Causes serious eye damage. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements (GHS)	 Do not breathe dust/fume/gas/mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor. Get medical advice/attention if you feel unwell. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
2.3. Other hazards No additional information available	
2.4. Unknown acute toxicity	
Not applicable	
SECTION 3: Composition/inform	mation on ingredients
3.1. Substances	
Not applicable	

Not applicable

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

3.2. Mixtures		
Name	Product identifier	%
Quartz	(CAS-No.) 14808-60-7	30 - 60 **
Aluminum oxide (Al2O3)	(CAS-No.) 1344-28-1	10 - 30
Calcium sulfate	(CAS-No.) 7778-18-9	7 - 13
Calcium oxide	(CAS-No.) 1305-78-8	5 - 10

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret ** (0.0025% respirable dust)

SECTION 4: First-aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
4.2. Most important symptoms and effect	ts, both acute and delayed
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause burns in the presence of moisture.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause damage to organs through prolonged or repeated exposure.
4.3. Indication of any immediate medica	I attention and special treatment needed
Symptoms may be delayed. In case of accident	or if you feel unwell, seek medical advice immediately (show the label where possible).
SECTION 5: Fire-fighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Not flammable. Not combustible.
Unsuitable extinguishing media	: Not necessary.
5.2. Special hazards arising from the su	bstance or mixture
Fire hazard	: Not combustible.
5.3. Advice for firefighters	
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
SECTION 6: Accidental release meas	sures
6.1. Personal precautions, protective eq	uipment and emergency procedures
General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
6.1.1. For non-emergency personnel No additional information available	
6.1.2. For emergency responders No additional information available	
6.2. Environmental precautions	
Prevent entry to sewers and public waters.	
6.3. Methods and material for containme	
For containment	: Contain spill, then place in a suitable container. Minimize dust generation. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Methods for cleaning up	: Sweep or shovel spills into appropriate container for disposal. Allow product to cool and solidify. Provide ventilation.
6.4. Reference to other sections	
For further information refer to section 8: "Exposu	re controls/personal protection"
SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Precautions for safe handling	: Avoid contact with skin and eyes. Do not breathe dust, fume, gas, mist, spray, vapours. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Good housekeeping is important to prevent accumulation of dust.
Hygiene measures	: Wash contaminated clothing before reuse. Wash hands, forearms and face thoroughly after handling.
7.2. Conditions for safe storage, including	g any incompatibilities
Storage conditions	: Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a dry, cool and well-ventilated place. Protect from physical damage.

SECTION 8: Exposure controls/personal protection

3.1. Control parameters		
Calcium oxide (1305-78-8)		
ACGIH	ACGIH TWA (mg/m³)	2 mg/m³
ACGIH	Remark (ACGIH)	URT irr
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
IDLH	US IDLH (mg/m ³)	25 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	2 mg/m ³
Quartz (14808-60-7)		
ACGIH	ACGIH TWA (mg/m³)	0.025 mg/m ³ (respirable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m ³)	50 μg/m³ (Respirable crystalline silica)
OSHA	Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m3 / (%SiO2+2)) for mg/m3. CAS No. source: eCFR Table Z-1.
NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
Aluminum oxide (Al2O3) (13	44-28-1)	·
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m³ (total dust) 5 mg/m³ (respirable fraction)
Calcium sulfate (7778-18-9)		
ACGIH	ACGIH TWA (mg/m³)	10 mg/m ³ (inhalable particulate matter)
OSHA	OSHA PEL (TWA) (mg/m³)	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
NIOSH	NIOSH REL (TWA) (mg/m³)	10 mg/m³ (total dust) 5 mg/m³ (respirable dust)

8.2. Exposure controls	
Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Wear suitable gloves.
Eye protection	: Wear eye/face protection.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

SECTION 9: Physical and chemical properties		
9.1. Information on basic physical and o	chemical properties	
Physical state	: Solid	
Appearance	: Gray powder	
Colour	: Gray	
Odour	: Odourless	
Odour threshold	: Not applicable	
рН	: 10-12	
Melting point	: Not applicable	
Freezing point	: Not applicable	
Boiling point	: Not applicable	
Flash point	: Not applicable	
Relative evaporation rate (butylacetate=1)	: Not applicable	
Flammability (solid, gas)	: Not flammable.	
Vapour pressure	: Not applicable	
Relative vapour density at 20 °C	: Not applicable	
Relative density	: 1.3	
Solubility	: Insoluble.	
Partition coefficient n-octanol/water	: Not applicable	
Auto-ignition temperature	: Not applicable	
Decomposition temperature	: Not applicable	
Viscosity, kinematic	: Not applicable	
Viscosity, dynamic	: Not applicable	
Explosive limits	: Not applicable	
Explosive properties	: Not applicable	
Oxidising properties	: Not applicable	
9.2. Other information		

VOC content

: Below detection limit

SECTION 10: Stability and reactivity
10.1. Reactivity
No dangerous reactions known under normal conditions of use.
10.2. Chemical stability
Stable under normal conditions.
10.3. Possibility of hazardous reactions
No dangerous reactions known under normal conditions of use.
10.4. Conditions to avoid
Heat. Direct sunlight. Incompatible materials. Moisture. Protect from physical damage.
10.5. Incompatible materials
Strong acids. Strong bases. Strong oxidizing agents.
10.6. Hazardous decomposition products
Will not spontaneously occur. Adding water produces caustic calcium hydroxide.
SECTION 11: Toxicological information
11.1. Information on toxicological effects

11.1.	Information on toxicological effects	S	
Acute	toxicity (oral)	:	Not classified.
Acute	toxicity (dermal)	:	Not classified.
Acute	toxicity (inhalation)	:	Not classified.
Skin c	orrosion/irritation	:	Not classified.
Seriou	us eye damage/irritation	:	Causes serious eye damage.
Respir	ratory or skin sensitisation	:	Not classified.
Germ	cell mutagenicity	:	Not classified.

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

cording to the Hazard Communication Standard (CFR29	9 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015
Carcinogenicity	: No causal association between this product exposure and cancer has been established, but Silica, Quartz (CAS# 14808-60-7), one of the ingredients is listed as a carcinogen by IARC and NTP. The respirable dust is lower than 0.003% in this product. It is lower than the GHS classification concentration limit(≥0.1%), so the product is not classified a as carcinogen.
Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Not classified.
Reproductive toxicity	: Not classified.
STOT-single exposure	: Not classified.
Calcium oxide (1305-78-8)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified.
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause burns in the presence of moisture.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	 May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
	diamea.
Chronic symptoms	: May cause damage to organs through prolonged or repeated exposure.
Chronic symptoms Other information	
Other information	: May cause damage to organs through prolonged or repeated exposure.
Other information SECTION 12: Ecological information	: May cause damage to organs through prolonged or repeated exposure.
Other information SECTION 12: Ecological information	: May cause damage to organs through prolonged or repeated exposure.
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye.
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8)	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment.
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye.
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 Calcium sulfate (7778-18-9)	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 LC50 fish 1 LC50 fish 1 LC50 fish 2	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 LC50 fish 1 LC50 fish 1 LC50 fish 2 2.2. Persistence and degradability	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 Calcium sulfate (7778-18-9) LC50 fish 1 LC50 fish 2 2.2. Persistence and degradability CN2000B Waterproof Material	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) > 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 Calcium sulfate (7778-18-9) LC50 fish 1 LC50 fish 1 LC50 fish 2 2.2. Persistence and degradability CN2000B Waterproof Material Persistence and degradability	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 Calcium sulfate (7778-18-9) LC50 fish 1 LC50 fish 2 2.2. Persistence and degradability CN2000B Waterproof Material Persistence and degradability 2.3. Bioaccumulative potential	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) > 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 Calcium sulfate (7778-18-9) LC50 fish 1 LC50 fish 2 2.2. Persistence and degradability CN2000B Waterproof Material Persistence and degradability 2.3. Bioaccumulative potential CN2000B Waterproof Material	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) > 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) Not established.
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 Calcium sulfate (7778-18-9) LC50 fish 1 LC50 fish 1 LC50 fish 2 2.2. Persistence and degradability CN2000B Waterproof Material Persistence and degradability 2.3. Bioaccumulative potential CN2000B Waterproof Material Bioaccumulative potential	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) > 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
Other information SECTION 12: Ecological information 12.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 Calcium sulfate (7778-18-9) LC50 fish 1 LC50 fish 1 LC50 fish 2 12.2. Persistence and degradability CN2000B Waterproof Material Persistence and degradability 12.3. Bioaccumulative potential CN2000B Waterproof Material Bioaccumulative potential Calcium oxide (1305-78-8)	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) > 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) Not established. Not established.
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 Calcium sulfate (7778-18-9) LC50 fish 1 LC50 fish 1 LC50 fish 2 2.2. Persistence and degradability CN2000B Waterproof Material Persistence and degradability 2.3. Bioaccumulative potential Bioaccumulative potential Bioaccumulative potential	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) > 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) Not established.
Other information SECTION 12: Ecological information 12.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 Calcium sulfate (7778-18-9) LC50 fish 1 LC50 fish 1 LC50 fish 2 12.2. Persistence and degradability CN2000B Waterproof Material Persistence and degradability 12.3. Bioaccumulative potential CN2000B Waterproof Material Bioaccumulative potential Calcium oxide (1305-78-8)	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) > 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) Not established. Not established.
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 Calcium sulfate (7778-18-9) LC50 fish 1 LC50 fish 2 2.2. Persistence and degradability CN2000B Waterproof Material Persistence and degradability 2.3. Bioaccumulative potential CN2000B Waterproof Material Bioaccumulative potential CN2000B Waterproof Material Bioaccumulative potential CAlcium oxide (1305-78-8) BCF fish 1	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) > 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) Not established. Not established.
Other information SECTION 12: Ecological information 2.1. Toxicity Ecology - general Calcium oxide (1305-78-8) LC50 fish 1 Calcium sulfate (7778-18-9) LC50 fish 1 LC50 fish 2 2.2. Persistence and degradability CN2000B Waterproof Material Persistence and degradability 2.3. Bioaccumulative potential CN2000B Waterproof Material Bioaccumulative potential Calcium oxide (1305-78-8) BCF fish 1 2.4. Mobility in soil	 May cause damage to organs through prolonged or repeated exposure. Likely routes of exposure: ingestion, inhalation, skin and eye. May cause long-term adverse effects in the aquatic environment. 1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static]) 2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) > 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) Not established. Not established.

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14: Transport information

Department of Transportation (DOT) and Transportation of Dangerous Goods (TDG)

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

In accordance with DOT/TDG

Not classified as dangerous goods

SECTION 15: Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories

15.2. International regulations

No additional information available

15.3. US State regulations

A WARNING:

This product can expose you to Quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information	
Revision date	: 12/13/2019
Other information	: Manufacturers Notes:
	The information on this data sheet reflects the currently available knowledge and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product, including the use of the product in combination with any other product or any other process, is the responsibility of the user. It is implicit that the user is responsible for determining appropriate safety measures and for applying the legislation covering his own activities.
Prepared by	: Nexreg Compliance Inc.
	www.Nexreg.com

SDS HazCom 2012 - WHMIS 2015 (NexReg)

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.